

## Zylindersicherungen aM

### Kapselsicherungen aM mit Kennmelder

geprüftes Schaltvermögen:

- 80kA – 690V
- 120kA – 400V
- 120kA – 500V



## Sicherungen nach französischem Standard

Größe	Bemessungsstrom in A	Bemessungsspannung in V	Verlustleistung bei I <sub>n</sub> in W	Teilenummer	Referenznummer	Gewicht in g/Stück	VE
10x38	1	500	0,13	X219233	16711	8	10
10x38	2	500	0,20	G222209	16713	8	10
10x38	4	500	0,30	K200753	16719	8	10
10x38	6	500	0,45	K201811	16723	8	10
10x38	8	500	0,55	Z211553	16727	8	10
10x38	10	500	0,65	H213102	16731	8	10
10x38	12	500	0,75	D214110	16733	8	10
10x38	16	500	0,90	P215132	16735	8	10
10x38	20	500	1,10	V216655	16737	8	10
10x38	25	400	1,40	L217682	16739	8	10
14x51	1	690	0,18	C212591	17711	19	10
14x51	2	690	0,25	M213106	17713	19	10
14x51	4	690	0,40	J214115	17719	19	10
14x51	6	690	0,55	T215136	17723	19	10
14x51	8	690	0,65	A216660	17727	19	10
14x51	10	690	0,75	R217687	17731	19	10
14x51	12	690	0,85	Q218721	17733	19	10
14x51	16	690	1,20	F219770	17735	19	10
14x51	20	690	1,50	R200759	17737	19	10
14x51	25	690	1,80	Q201816	17739	19	10
14x51	32	500	2,10	F211559	17743	19	10
14x51	40	500	2,60	D212592	17747	19	10
14x51	45	500	2,60	G231607	17749	19	10
14x51	50	400	2,90	M214624	17751	19	10
22x58	4	690	0,50	L219246	18719	51	10
22x58	6	690	0,65	V222221	18723	51	10
22x58	8	690	0,75	Y201823	18727	51	10
22x58	10	690	0,85	N211566	18731	51	10
22x58	12	690	1,00	K212598	18733	51	10
22x58	16	690	1,40	P213614	18735	51	10
22x58	20	690	1,70	V214631	18737	51	10
22x58	25	690	2,00	D215651	18739	51	10
22x58	32	690	2,60	J216668	18743	51	10
22x58	40	690	3,20	Z217694	18747	51	10
22x58	50	690	3,90	P219778	18751	51	10
22x58	63	690	4,60	Z200766	18755	51	10
22x58	80	690	5,60	P211567	18759	51	10
22x58	100	500	6,50	L212599	18763	51	10
22x58	125	400	9,50	W214632	18765	51	10