

## Sicherungen nach französischem Standard

## Zylindersicherungen aM

**Kapselsicherungen aM  
mit Schlagbolzen**

geprüftes Schaltvermögen:

80kA – 690V  
120kA – 400V  
120kA – 500V

Größe	Bemessungsstrom in A	Bemessungsspannung in V	Verlustleistung bei I <sub>N</sub> in W	Teile-Nummer	Referenz-Nummer	Gewicht in g/Stück	VE
14x51	1	500	0,18	W215644	17911	18	10
14x51	2	500	0,25	B216661	17913	18	10
14x51	4	500	0,40	C218203	17919	18	10
14x51	6	500	0,55	E219240	17923	18	10
14x51	8	500	0,65	N222215	17927	18	10
14x51	10	500	0,75	S200760	17931	18	10
14x51	12	500	0,85	R201817	17933	18	10
14x51	16	500	1,20	G211560	17935	18	10
14x51	20	500	1,50	E212593	17937	18	10
14x51	25	500	1,80	H213608	17939	18	10
14x51	32	500	2,10	N214625	17943	18	10
14x51	40	500	2,60	X215645	17947	18	10
14x51	45	500	2,80	C216662	17949	18	10
14x51	50	400	2,90	D218204	17951	18	10
22x58	1	690	0,20	E215652	18911	51	10
22x58	2	690	0,30	J216162	18913	51	10
22x58	4	690	0,50	A217695	18919	50	10
22x58	6	690	0,65	Y218728	18923	50	10
22x58	8	690	0,75	Q219779	18927	50	10
22x58	10	690	0,85	S222978	18931	51	10
22x58	12	690	1,00	R201311	18933	50	10
22x58	16	690	1,40	W211044	18935	50	10
22x58	20	690	1,70	W212079	18937	50	10
22x58	25	690	2,00	Q213615	18939	50	10
22x58	32	690	2,60	X214633	18943	51	10
22x58	40	690	3,20	F215653	18947	51	10
22x58	50	690	3,90	K216669	18951	51	10
22x58	63	500	4,60	B217696	18955	51	10
22x58	80	500	5,60	Z218729	18959	51	10
22x58	100	500	6,50	T222979	18963	51	10
22x58	125	400	9,50	S201312	18965	51	10