



Zylindersicherungen gL-gG

Sicherungen nach französischem Standard

Kapselsicherungen gL-gG ohne Kennmelder

geprüftes Schaltvermögen:

80kA – 690V
120kA – 400V
120kA – 500V



Größe	Bemessungsstrom in A	Bemessungsspannung in V	Verlustleistung bei I _n in W	Teile-Nummer	Referenz-Nummer	Gewicht in g/Stück	VE
10x38	0,5	500	0,20	C211027	16009	8	10
10x38	1	500	0,60	B212061	16011	8	10
10x38	2	500	0,70	D213098	16013	8	10
10x38	4	500	0,80	X213598	16019	8	10
10x38	6	500	0,90	K215128	16023	8	10
10x38	8	500	1,10	D217169	16027	8	10
10x38	10	500	1,35	S218194	16031	8	10
10x38	12	500	1,55	W219761	16033	8	10
10x38	16	500	1,90	G200750	16035	8	10
10x38	20	500	2,30	D211028	16037	8	10
10x38	25	500	2,80	E213099	16039	8	10
10x38	32	400	3,00	A214107	16043	8	10
14x51	1	690		K218716	17011	10	10
14x51	2	690	1,00	Y219234	17013	10	10
14x51	4	690	1,10	A219765	17019	10	10
14x51	6	690	1,20	H222210	17023	10	10
14x51	8	690	1,50	D222965	17027	10	10
14x51	10	690	1,80	L200754	17031	10	10
14x51	12	690	2,10	L201812	17033	10	10
14x51	16	690	2,55	A211554	17035	10	10
14x51	20	690	3,00	Z212588	17037	10	10
14x51	25	690	3,50	C213603	17039	10	10
14x51	32	500	3,80	W216656	17043	10	10
14x51	40	500	4,40	X218198	17047	10	10
14x51	50	400	4,70	Z219235	17051	10	10
22x58	2	690	1,20	F219241	18013	51	10
22x58	4	690	1,30	H219772	18019	51	10
22x58	6	690	1,40	P222216	18023	51	10
22x58	8	690	1,65	L222972	18027	51	10
22x58	10	690	2,00	T200761	18031	51	10
22x58	12	690	2,40	J201304	18033	50	10
22x58	16	690	3,00	S201818	18035	51	10
22x58	20	690	3,40	P211038	18037	51	10
22x58	25	690	3,80	N212072	18039	50	10
22x58	32	690	4,30	F212594	18043	50	10
22x58	40	690	5,10	J213609	18047	50	10
22x58	50	690	5,50	P214626	18051	50	10
22x58	63	690	6,70	Y215646	18055	50	10
22x58	80	690	8,00	Q217180	18059	51	10
22x58	100	500	9,00	E218205	18063	50	10
22x58	125	400	12,50	J219773	18065	50	10