



Maßzeichnungen

Zweckleuchten


LISILUX-Deckenleuchte




LISILUX-Wandleuchte




LISILUX-Ersatzschraubglas




Saunaleuchte 6061




UNIFIX-Deckenleuchte




UNIFIX-Wandleuchte




ELDECO-Deckenleuchte




ELDECO-Deckeneinbauleuchte




Deckenleuchte 6513




Totalglasleuchte



Kugelglas



Zylinderglas



ReferenzNr.	a	b	c	d	e*
400.02	-	-	94	-	-
400.62	83	130	94	-	-
400.72	83	130	94	-	-
407.02	-	-	105	-	-
407.62	95	130	105	-	-
407.72	95	130	105	-	-
401	-	-	-	-	60
401.6	76 x 50	120	83	136	60
401.7	76 x 60	120	83	136	60
408.6	88 x 62	123	95	138	68
408.7	88 x 62	123	95	138	68
308.02	-	-	124	-	-
308.62	112	174	124	-	-
308.72	112	174	124	-	-
310.02	165	224	150	-	-
402.6	120	158	-	-	-
403.6	72	160	120	180	-
412.6	120	158	-	-	-
6401.1	680	120	-	-	38
6431.1	800	82	-	-	-
970.002102	-	-	-	-	70
5091	110	250	145	-	-
5092	110	300	165	-	-
6513.100012	125	167	-	-	-
6061.701012	98 x 76	174	95	130	72
400.620035	83	130	94	-	-
400.720035	83	130	94	-	-
401.700035	76 x 60	120	83	135	60
400.09	68	82	-	-	-
400.090035	68	82	-	-	-
407.09	77	91	-	-	-
308.09	96	112	-	-	-
310.09	118	134	-	-	-
11	83	102	74,5	-	-
11.7	83	102	74,5	-	-
12	95	102	84,5	-	-
12.70	95	102	84,5	-	-
13	112	135	99	-	-
13.7	112	135	99	-	-
168	125	130	74,5	-	-
127	150	153	84,5	-	-
128	180	185	99	-	-
129	215	222	123,5	-	-
1945	95	170	84,5	-	-
1946	112	180	99	-	-

Maße in mm, e\* = Befestigungslochabstand